



ABR - SIDEWINDER



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE OR PERSONAL INJURY, AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

This is a quick start guide only, please follow the instructions in the manufacturers instructions and take note of warnings and important information regarding this product.

2. INTRODUCTION

Charge the monitor with the supplied cable and fit the batteries to the sensors. Take note the (+) faces outwards on the sensor batteries. Label the sensors for ease of use with a suitable marker.

3. OPERATION

Note: Do not fit the sensors yet.

1) Turn the monitor on by pressing the center button for 2 seconds.

2) Enter sensor alignment mode by pressing both outer buttons at the same time for 3 seconds.

Use the 2 outer buttons to cycle through the sensor positions on the monitor and stop at the position you would like to align the sensor to. Screw the labeled sensor to that tyre.

Repeat this process with the other sensors.

To delete a sensor or sensor position simply hold down the center button while displaying that sensor position.

Exit by holding down the two outer buttons at the same time for 5 seconds.

3) Once the sensors are aligned the system will show '**noS**' until all sensors register and set up a link with the monitor. This may take 5 to 8 minutes.

4) Set the monitor warning limits:

Limits can be set and adjusted at any time even when the screen displays '**noS**'

Note: Temperature is not settable as it is preset at factory. (75 deg Alarm 1 and 85 deg Alarm 2)

Press and hold the center button for 5 seconds.

Use the center button to cycle through the sensor positions.

Use the outer buttons to increase or decrease the pressure setting.

(Set the pressure to 10% higher than your cold tyre pressures.)

Exit by holding down the center button for 3 seconds.

5) Turn the monitor off by holding the center button down for 8 seconds.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product. **WARRANTY:** 12 months from date of purchase - Proof required.

This product is for private recreational use and is not to be used in commercial or competition environments.

